



A Division of NSS Enterprises, Inc.

Phone: 800.889.4049
Fax: 419.578.2274
3115 Frenchmens Road
Toledo, Ohio 43607-2958
www.milagon.com

Engineered for Work.™
Ergonomic Chairs & Mats

ERGO MATTA

Industrial and Commercial Safety Surfacing





Ergo Matta is an excellent matting system where traffic volume is relatively high and under foot stability is required. Increased versatility is achieved by utilizing half sized mats. Ergo Matta is easily removed for areas that require frequent cleaning. Ergo Matta contains an anti-microbial additive that inhibits fungal growth making it ideal for use in wet areas.

- Excellent ergonomic and anti-fatigue qualities
- Easy to clean surface
- Unique interlocking design allows system to be rolled up for ease of cleaning
- Available in open and closed configurations.
- Safety yellow or black edge ramps and mitered corners
- Ideal for use at workstations, locker rooms, showers, and recreational facilities.
- Made from recycled material

ERGO MATTA

Industrial and Commercial
Safety Surfacing

	Model #	
Ergo Matta Open 	EMOB11	The Ergo Matta tile systems allow for a multitude of uses such as service counters, locker rooms, & showers. Each tile is 10" x 20" x 9/16" and can be configured to any size area. The tiles offer excellent ergonomic benefits, and the open and closed tiles are designed to interlock securely with each other.

	Model #	
Ergo Matta Closed 	EMCB1	Ergo Mattas contain an anti-microbial to combat fungal growth. Safety edge ramps are available for easy entry onto the flooring surface. Ergo Mattas allow each installation to be tailored to meet the individual needs of any facility and provide an attractive and permanent appearance.

Specifications:

Product	Dimensions	Thickness	Weight	Color	Material	Shore Hardness	Temperature Variation	Interlocking Connection	Average Coefficient of Friction ASTM E303-93 (Reproved 1998)
EMOB11	10"x20"	9/16"	4 lbs.	Black	PVC	75	-22° TO 140°F	6 Lug	31 Wet / 31 Dry
EMCB1	10"x20"	9/16"	6.3 lbs	Black	PVC	75	-22° TO 140°F	6 Lug	29 Wet / 29 Dry

ADA Compliance ASTM F 1951-99	Ultra Violet Stabilized	Fire Exposure Test ASTM E108
75	Yes	PASSED
75	Yes	PASSED